


HT-Net604

Entry Network Appliance Platform with Intel® Atom™ processor N450 and 4LANs



Features

Low power and high performance Intel® Atom™ processor N450 1.66 GHz with 512K L2 cache

Supports 4 x 10/100/1000Mbps Ethernet ports

Supports 2 SATAII HDD

Suitable for VPN, network bandwidth controller, firewall applications

Supports Intel® Hyper-threading technology

Specifications

CPU	Intel® Atom™ processor N450 1.66 GHz with 512K L2 cache
Chipset	Intel® Pineview+NM10
Memory	DDRII 667, up to 2GB
BIOS	AMI 4Mbit PnP Flash BIOS
Storage	2 x SATAII HDD
Network Interface	4x 10/100/1000Mbps Ethernet
I/O Interface	1 x RS-232 DB9 connector, 2 x USB connector, 4 x RJ-45 connector, 1 x DC-in power jack
USB	2 x USB 2.0 port in the rear side, others are pin header internally
Power	1 x 12V, 5A power adapter
OS Compatibility	Linux Redhat Kernel 2.6
Form Factor	1U desktop or Rackmount
LED	Power, HDD, Link/Act with transfer rate
Operating Temp.	0°C ~ +45°C (32°F ~ 113°F)
Storage Temp.	20°C ~ +70°C (-4°F ~ +158°F)
Humidity	10% ~ 95% RH, non-condensing
Chassis Material	Steel
Dimensions	WxDxH:
Weight	2.5 kg