

## HT-Net660

## Entry Network Appliance Platform with Intel® Atom™ D525 Dual Core/ D425 Single Core 1.8GHz Processor and 6 GbE LANs



**(Only reference, not release)**

### Features

1U Rackmount Network Platform

Support Intel® Atom™ D525 Dual Core/ D425 Single Core 1.8GHz Processor

Support 6 x 10/100/1000Mbps PCIe Ethernet ports

Support LAN Bypass

Internal one 3.5" HDD Bay/ two 2.5" HDD Bay (Optional)

### Specifications

<b>Form Factor</b>	1U Rackmount
<b>CPU</b>	Intel® Atom™ D525 Dual Core/ D425 Single Core 1.8GHz Processor
<b>Chipset</b>	Intel® PineviewD+ICH8M
<b>Memory</b>	1 x 204-pin DDR3 800 SO-DIMM Socket, up to 2GB Non-ECC SDRAM
<b>BIOS</b>	AMI 4Mbit PnP Flash BIOS
<b>Storage</b>	2 x SATAII HDD(MainBoard) Internal one 3.5" HDD Bay/ two 2.5" HDD Bay (Optional) 1 x CompactFlash Socket
<b>Network Interface</b>	LAN Chip: Intel® 82574L 6x 10/100/1000Mbps Ethernet LAN Bypass: 1 pairs
<b>Front I/O</b>	Power /HDD /LAN /Bypass status LED 2 x USB2.0 connector 6 x Copper LAN ports 1 x RJ45 type Console
<b>Rear I/O</b>	1 x VGA
<b>Expansion</b>	1 x PCI Slot
<b>Power</b>	150W ATX Power supply
<b>OS Compatibility</b>	Linux Redhat Kernel 2.6
<b>Operating Temp.</b>	0°C ~ +45°C (32°F ~ 113°F)
<b>Storage Temp.</b>	20°C ~ +70°C (-4°F ~ +158°F)
<b>Humidity</b>	10% ~ 95% RH, non-condensing

<b>Chassis Material</b>	Steel
<b>Dimensions</b>	WxDxH:
<b>Weight</b>	2.5 kg